



Specification:

- 1. Connector Type : LC/PC Multimode
- 2. Connector Type : SC/PC Multimode
- 3. Cable Type :
 - 3-1 Zipcord cable, $\varnothing 3.0\text{mm}$, 62.5/125um Multimode,
 - 3-2 Cable Jacket : Orange color, PVC material
- 4. Cable Marker
- 5. Shrink Tube
- 6. Length : xM

Performance:

- a. Insertion Loss : $< 0.5 \text{ dB}$
- b. Fiber Extension : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- c. Ferrule End-face Radius : $7 < R < 25\text{mm}$
- d. Apex Offset : $< 50\mu\text{m}$
- e. Increase in insertion loss after 500 mating : 0.2 dB Max.
- f. Operation Temperature : -20° to $+70^{\circ}$
- g. Storage Temperature : -40° to $+80^{\circ}$

GENERAL TOLERANCE OF DIMENSIONS X.XXX ± 0.005 X.XX ± 0.05 X.X ± 0.1	DRAWING	15.JUN.2007	Michelle	SFCable.com 1-888-275-8755	
	CHECK	15.JUN.2007	YTY		
	APPROVAL	15.JUN.2007	YTY		
		DATE	NAME	ITEM NO.: 60LC-SCXX	
	SCALE	1/1 (A4)	UNIT	mm	DES.: LC to SC Duplex patch cord
		DRAWING NO. 60LC-SCXX			
		DRAWING CLASSIFICATION	S	SHEET	1 OF 1