



MATERIAL LIST:

- 1 CABLE: UL2464+CSA 28AWG*25C+EA COLOR:BEIGE(P003)W920717024
- 2 CABLE: UL2464+CSA 28AWG*9C+EA COLOR:BEIGE(P003)W91111306
- 3 CONN: DB25 FEMALE TYPE SOLDER INSULATOR:BLUE NICKEL PLATED SHELL
- 4 CONN: DB25 MALE INSULATOR BLUE ~~MINI~~ TYPE SOLDER NICKEL PLATED SHELL
- 5 CONN: DB9 MALE INSULATOR BLUE ~~MINI~~ TYPE SOLDER NICKEL PLATED SHELL
- 6 THUMBSCREW:4*30.5mm COLOR:K003
- 7 PVC MOLDED: 45P COLOR:BEIGE(V820)

ELECTRONIC TEST:

- A. OPEN/SHORT/INTERMITTENCE 100% TEST.
- B. HI-POT: 350V AC/sec.
- C. INSULATION RESISTANCE: 20Mohm (MIN) at DC 500V.
- D. CONDUCTIVE RESISTANCE: 2ohm (MAX).

REV	ECN NO	DESCRIPTION	APPD.	DATE

QVS <small>The Quality Specialist</small>			
Tolerance:	Approved by:	Customer P/N:	
X. ±		CC2000Y	
.X ±		Checked by:	Space Shuttle P/N:
.XX ±		J00070562	
.XXX ±	Drawn by:	Description:	
Angle:	ft.cui	DB25F TO DB25M+DB9M	
X" ±	Date:	DWG. NO:	
.X" ±	2006.6.30		
	Scale:	Unit: mm	SHEET: 1 OF 3
			REV: 00