






NOTE: ALL MATERIAL COMPLIANT ROHS STANDARD

REVISION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description



SCALE 1/1



Specification :

Material :

1. RJ45 Jack Housing : ABS+PC, UL 94V-0, Black color.
2. RJ45 Jack Bracket Set : PC, UL 94V-2, Transparent color.
3. RJ45 Jack Contact & Finished :
 - 3-1. Material : Phosphor Bronze with Nickel plated.
 - 3-2. Finish : 50 micro-inch Gold plated on Plug contact area.
4. PCB : FR4, UL94V-0.

Performance :

- a. Insertion force : 20N max. (IEC 60603-7-4).
- b. Retention strength : 7.7 kg between Jack and Plug.
- c. Operating temperature : -10°C to 60°C.(ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- d. Life(mating cycles) : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-4).
- e. The Cat.5e transmission performance is in compliance with the ANSI/TIA/EIA 568 B.2 standard.

Remark : AAEAB00011311XX

(1)

(1) XX : Housing Color
01=Black, 05=White

SFCABLE.COM

NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT
③				
②				
①				

DRAWN BY	DATE: 2012/08/25	DESCRIPTION: Cat.5E Inline Coupler w/Keystone Latch Blue Cat.5E Inline Coupler w/Keystone Latch Blacke
CHECKED BY	SHEET 1 of 1	ITEM NO. 1020-SF-09
APPROVED BY	SCALE 1:1	REV. 00 UNIT: mm