


REVISION			
LTR	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	05/18/94	H.T.




CN36 Male



CN36 Male

Specification:

1. Voltage Rating: 300 VAC(rms).
2. Current Rating: 5 AMP Continuous.
3. Dielectric Strength: 1,000 VAC.
4. Insulation Resistance: 5,000 Mohm min.
5. Durability: 30 Cycles for Gold Flash,
150 Cycles for 15u Gold Plated.
6. Corrosion Resistance: Meet MIL-STD-202F Method
101 Condition B Salt Water. Spray for Gold Plated Over 15u.
7. Mating Force Insertion Force: 1 oz – 16 oz
Average 150 gram. Extraction Force: 1 KG min.

UNLESS OTHERWISE SPECIFIED: 1. DIMENSION ARE IN INCHS 2. TOLERANCES: DECIMALES X.XX ±0.25 3. DO NOT SCALE DRAWING 4. REMOVE ALL BURRS AND BREAK SHARP EDGES.	CUSTOMER		 sfcable.com 1-888-275-8755	
	R.F.Q. NO.			
	DRAWN	DATE	TITLE	
	Howie Tseng	05/18/94		
PROPRIETARY DOCUMENT THIS DRAWING AND/OR INFORMATION OR SUBJECT MATTER CONTAINED HEREIN, SHALL NOT BE USED, COPIED OR DISSEMINATED IN ANY MANNER, OR FOR ANY PURPOSE, OTHER THAN AS EXPRESSLY STATED BY	CHECKED		CN36, M/M, Mini Gender Changer	
	CUSTOMER APPROVAL			
	SIZE	DWG NO.	PART NO.	REV.
		10GC-J1	10GC-J1	A
SCALE: NONE		RELEASE DATE: 05/18/94	SHEET: 1 OF 1	