

REVISION			
LTR	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	05/18/94	H.T.



CN50 Female



Specification:

1. Voltage Rating: 300 VAC(rms).
2. Current Rating: 5 AMP Continuous.
3. Dielectric Strength: 1,000 VAC.
4. Insulation Resistance: 5,000 Mohm min.
5. Durability: 30 Cycles for Gold Flash,
150 Cycles for 15u Gold Plated.
6. Corrosion Resistance: Meet MIL-STD-202F Method
101 Condition B Salt Water. Spray for Gold Plated Over 15u.
7. Mating Force Insertion Force: 1 oz – 16 oz
Average 150 gram. Extraction Force: 1 KG min.



CN50 Female

UNLESS OTHERWISE SPECIFIED:
1. DIMENSION ARE IN INCHS
2. TOLERANCES:
DECIMALES X.XX ±0.25
3. DO NOT SCALE DRAWING
4. REMOVE ALL BURRS AND
BREAK SHARP EDGES.

PROPRIETARY DOCUMENT
THIS DRAWING AND/OR INFORMATION OR
SUBJECT MATTER CONTAINED HEREIN,
SHALL NOT BE USED, COPIED OR
DISSEMINATED IN ANY MANNER, OR FOR
ANY PURPOSE, OTHER THAN AS
EXPRESSLY STATED BY

CUSTOMER	
R.F.Q. NO.	
DRAWN	DATE
Howie Tseng	05/18/94
CHECKED	
CUSTOMER APPROVAL	

 1-888-275-8755			
TITLE			
CN50, F/F, Mini Gender Changer			
SIZE	DWG NO.	PART NO.	REV.
	10GC-L3	10GC-L3	A
SCALE: NONE	RELEASE DATE: 05/18/94	SHEET: 1 OF 1	