



8244-1

| P1 | | P2 | |
|----|--|----|--------------|
| 1 | | 3 | WHITE/ORANGE |
| 2 | | 6 | ORANGE |
| 3 | | 1 | WHITE/GREEN |
| 6 | | 2 | GREEN |
| 4 | | 4 | BLUE |
| 5 | | 5 | WHITE/BLUE |
| 7 | | 7 | WHITE/BROWN |
| 8 | | 8 | BROWN |

MARKING: 350MHz (UL) E305668 TYPE CMG 24AWG 75°C CSA 204790 CMG
 75°C FT4 ETL VERIFIED TIA/EIA-568-C.2 UTP CAT.5E RoHS COMPLIANCE BATCH NO.

⚠ * NOTE: All relevant materials are complied with RoHS directive .

| 3 | MOLDED PVC GRAY-WHITE | H1BP01-0304G07 | | M304 |
|----------|--------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------|----------|
| 2 | 4 TWISD PAIRS CAT.5E 24AWG(7/0.19AS) UTP, OD 5.3mm, JACKET GRAY-WHITE, DRAWING No. EU002404P-174 | H5AH21-0304G07 | L+10mm | M304 |
| 1 | 8P8C MODULAR PLUG, GOLD PLATING 50u" ON CONTACTS, SHORT TYPE | A1NA42-0209 | 2 | M209 |
| No. | DESCRIPTION | | Q'TY | Supplier |
| APPROVED | | Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm | | |
| CHECKED | HU | | | |
| DRAWING | ZHU | | | |
| DATE | 22/JUN/17 | | | |
| ITEM NO. | 10X5-332XX | UNIT:mm | | |