


NOTE: All relevant materials are complied with RoHS directive .

### UNC #4-40 Hexscrew



MA 005C (DB9M/M ADAPTER)

PIN OUT: 9Male		9Male
2	-----	3
3	-----	2
4	-----	1
5	-----	6
1	-----	5
6	-----	4
7	-----	8
8	-----	7
G	-----	G

Label: Orange color with white character

One side: NULL MODEM

The other side: MINI ADAPTER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin Plated Shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C +105°C

				Edition A1	PART NO. 30D1-C1-S	<b>SFCable.com</b> 888-275-8755				
				SCALE 2:1	UNLESS OTHERWISE SPECIFIED TOLERANCES: 0.0: ±0.20 0.00: ±0.13 0.000: ±0.08					
	1	修改螺絲(螺絲5.2mm改為6.2mm)	2003/07/02	UNIT mm						
Customer	REVISION	DESCRIPTION	DATE	PAGE 1/1		DRAWN <i>Jw Hoo</i>	CHECKED		APPROVED	