



MA 001C (DB9M/25M ADAPTOR)

PIN OUT: 09Male 25Male

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character
 One side: SERIAL PORT ADAPTORS D9/D25
 The other side: MINI ADAPTER
 SPECIFICATION
 INSULATOR: PBT Glass fibre reinforced UL 94 V0
 CONTACT: Brass
 CONTACT PLATING: Gold plated over nickel
 SHELL: Tin plated shell (Nickel Silver)
 CURRENT RATING: 3 AMP
 DIELECTRIC STRENGTH: 500V AC for one minute
 INSULATOR RESISTANCE: 500MΩ min at 500V DC
 TEMPERATURE: -25°C—+105°C

NOTE: All relevant materials are complied with RoHS directive .

				Edition	SFCable.com				
				A01					
				SCALE	UNLESS OTHERWISE SPECIFIED TOLERANCES: 0.0: ±0.20 0.00: ±0.15 0.000: ±0.05		PART NO.	DWG NO.	DATE
				2:1			31D1-26100	TM0053-02	8/Dec-2001
				UNIT			DRAWN	CHECKED	APPRD
				mm					
Customer	REVISION	DESCRIPTION	DATE	Page	1/1				
	1	修改貼紙(R.O.C. PATENT 105471 改為 MINI ADAPTER)	2001/12/8						