



MA 001A (DB9M/25F ADAPTOR)

PIN OUT: 09Male

25Female

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell (Nickel Silver)

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C—+105°C

NOTE: All relevant materials are complied with RoHS directive .

				Edition	SFCable.com				
				A01					
				SCALE	UNLESS OTHERWISE SPECIFIED TOLERANCES: 0.3: 0.20 0.50: 0.15 0.800: 0.02		PART NO.	DRG NO.	DATE
				2:1			31D1-26200	TMO051-02	8/Dec-2001
				UNIT			DRAWN	CHECKED	APPRD
				mm					
Customer	REVISION	DESCRIPTION	DATE	Page	1/1				
	1	修改图纸(R.O.C. PATENT 105471 改為 MINI ADAPTER)	2001/12/8						