



MA 001B (DB9F/25M ADAPTOR)

PIN OUT: 09Female

25Male

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C—+105°C

NOTE: All relevant materials are complied with RoHS directive.

				Edition	SFCable.com				
				A01					
				SCALE	<small>SCALE (mm)</small> <small>0.1: 25.40</small> <small>0.50: 25.40</small> <small>1.00: 25.40</small> <small>2.00: 50.80</small>		PART NO.	DWG NO.	DATE
				2:1			31D1-26300	TM0052-02	8/Dec-2001
				UNIT			DRAWN	CHECKED	APPRD
				mm					
Customer	REVISION	DESCRIPTION	DATE	Page	1/1				
	1	修改規格(R.O.C. PATENT 105471 改為 MINI ADAPTER)	2001/12/8						