



MA 001D (DB9F/25F ADAPTOR)

PIN OUT: 09Female 25Female

1	-----	8
2	-----	3
3	-----	2
4	-----	20
5	-----	7
6	-----	6
7	-----	4
8	-----	5
9	-----	22
G	-----	G

Label: orange color with white character

One side: SERIAL PORT ADAPTORS D9/D25

The other side: MINI ADAPTER

SPECIFICATION

INSULATOR: PBT Glass fibre reinforced UL 94 V0

CONTACT: Brass

CONTACT PLATING: Gold plated over nickel

SHELL: Tin plated shell

CURRENT RATING: 3 AMP

DIELECTRIC STRENGTH: 500V AC for one minute

INSULATOR RESISTANCE: 500MΩ min at 500V DC

TEMPERATURE: -25°C—+105° C

NOTE: All relevant materials are complied with RoHS directive .

				Edition	SFCable.com					
				A01						
				SCALE	<small>UNLESS OTHERWISE SPECIFIED DIMENSIONS:</small> 0.0: 10.20 0.10: 10.13 0.000: 10.05		PART NO.	DRG NO.	DATE	
				2:1			31D1-26400		TM0054-02	8/Dec-2001
				UNIT						
				mm			1/1			
Customer	REVISION	DESCRIPTION	DATE							
	1	修改名称(B.O.C. PATENT 105471 改为 MINI ADAPTER)	2001/12/8							