



RJ45 F (I/O)	6070 SWITCH	RJ45 F A&B
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
8	8	8

*NOTE: All relevant materials are complied with RoHS directive .

6	PLASTO-VISCO-ELASTIC BODY	4	M562
5	SCREW 3*6PWB	4	M805
4	METAL CASE, THICKNESS 0.8mm	1set	M315
3	UL1061 26AWG INSULATOR, LENGTH 150mm	24	M541
	MAIN HEART 1-B-2	1	M94
	SCREW 4*12.5mm WITH PAD	1set	M94
2	KNOB FOR A, B. SWITCH	1	M94
	STATOR	1	M348
	PCB: RJ-45	1	M590
1	HEX-NUT WITH SCREW CAP 3*6mm	2set	M95
	RJ45 FEMALE, GOLD FLASH ON CDNTACTS	3	M22
No.	DESCRIPTION	Q'TY	Supplier

APPROVED		SFCable.com	Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm± ±40mm
CHECKED	TIAN		
DRAWING	LI		
DATE	21/JUL/08		
ITEM NO.	40R2-A2	UNIT:mm	

CHECKED