



Specification:

1. Connector Type : LC/PC Multimode
2. Cable Type :
 - 2-1 Zipcord cable, $\phi 3.0\text{mm}$, 62.5/125um Multimode,
 - 2-2 Calbe Jacket : Orange color, PVC material
3. Cable Marker
4. Shrink Tube
5. Length : xM

Performance:

- a. Insertion Loss : $< 0.5 \text{ dB}$
- b. Fiber Extention : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- c. Ferrule End-face Radius : $7 < R < 25\text{mm}$
- d. Apex Offset : $< 50\mu\text{m}$
- e. Increase in insertion loss after 500 mating : 0.2 dB Max.
- f. Operation Temperature : -20° to $+70^{\circ}$
- g. Storage Temperature : -40° to $+80^{\circ}$

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	12.FEB.2004	Michelle	SFCable.com 1-888-275-8755
	CHECK	12.FEB.2004	YTY	
	APPROVAL	12.FEB.2004	Magic	
		DATE	NAME	ITEM NO.: 60LC-LCXX
SCALE	1/1 (A4)	UNIT	mm	DES.: LC to LC Duplex patch cord
©	DRAWING NO.	60LC-LCXX		
	DRAWING CLASSIFICATION	S	SHEET	1 OF 1

