



| 8233-35 | |
|---------|----------------|
| P1 | P2 |
| 1 | 1 WHITE/ORANGE |
| 2 | 2 ORANGE |
| 3 | 3 WHITE/GREEN |
| 6 | 6 GREEN |
| 4 | 4 BLUE |
| 5 | 5 WHITE/BLUE |
| 7 | 7 WHITE/BROWN |
| 8 | 8 BROWN |

MARKING: ⚠ ⚠ ⚠ ⚠ ⚠ ⚠

(UL) E305668 TYPE CM 28AWG 75°C C(UL) E305668
 CM 28AWG 75°C ETL VERIFIED ANSI/TIA-568.2-D
 MINI UTP CAT.6 RoHS COMPLIANCE MSL-VN- BATCH NO. ⚠

*NOTE: All relevant materials are complied with RoHS directive . ⚠

| ⚠ | 3 | 8P8C TRANSPARENT BOOT(OD4.5mm) | A4FK36-0209 | 2 | M209 |
|-----|-------------|---|----------------|--------|----------|
| | 2 | 4 TWISD PAIRS MINI CAT.6 28AWG UTP, OD 3.6mm, JACKET BLUE(UH-4), DRAWING No.EU002804P-643 | H5AJ33-0304U07 | L+10mm | M304 |
| ⚠ ⚠ | 1 | 8P8C MODULAR PLUG, GOLD PLATING 50u" ON CONTACTS, NO.P8-063-11 | A1NC36-0209 | 2 | M209 |
| No. | DESCRIPTION | | | Q'TY | Supplier |

| | | | | | |
|----------|-----------|---|---|---------|---|
| APPROVED | |  <p>SFCable</p> <p>1-888-275-8755</p> | Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm | | |
| CHECKED | HU | | | | |
| DESIGNER | XJW | | | | |
| DRAWING | WEI | | | | |
| DATE | 10/MAR/23 | ITEM NO. | CAT6-SL-XX-28AWG | UNIT:mm |  |

| | | | | | |
|--------------------|----------------|--------------------|---|---------|--|
| ⚠ REV.9 2023.3.10 | MODIFY MARKING | | | | |
| ⚠ REV.7 2021.03.11 | MODIFY MARKING | ⚠ REV.8 2021.08.20 | MODIFY MARKING AND MODIFY PLUG SUPPLIER | | |
| ⚠ REV.5 2019.07.02 | MODIFY MARKING | ⚠ REV.6 2019.10.21 | 8P 8C TRANSPARENT BOOT SUPPLIER | | |
| ⚠ REV.3 2016.04.28 | MODIFY MARKING | ⚠ REV.4 2018.11.20 | MODIFY MARKING | | |
| ⚠ REV.1 2015.12.08 | MODIFY PLUG | ⚠ REV.2 2015.12.17 | ADD MARKING | CHECKED | |