



● 100% OPEN / SHORT / INSULATING TEST

● INSULATION TEST: 2MΩ

COMPONENTS	DESCRIPTION	QTY
1	DVI-D 18M DVI-Digital 18P Male Connector Insulator: High Temperature Plastic UL-94V-0 Contact: Brass Shell: Steel With Tin Plated 150µ" Over Contact Plating: G/F Selective Plating And Tin/LEAD On Solder Cup All With Nickel Underplating	1
2	Jackscrew UNC #4-40 Nickel Plated Hood: ABS Color: Black	2
3	Hood Assembly Hood: Outer P.V.C Molded Color: Black Inner Shell Material: SPCC	1
4	Cable D7384 (DER AN) UL20276 80°C 30V OD: 7.3mm Color: Black L: 1830mm	1
5	FMC20M Half Pitch Centronic 20P Male Connector Shell: Steel Nickel Plated Insulator: Black P.B.T Contact: Phosphor Bronze 5µ" Gold Plated	1
6	Hood Outer Hood: ABS Color: Black Inner Shell: Steel Nickel Plated	1
7	Latch Spring Latch Hood: ABS Color: Black	2

QVS
The Connectivity Specialist™

DESCRIPTION:
DVI to DFP Adaptor Cable
(6ft Cable Shown)

APPROVED BY:	DATE:
	11.28.2000
CHECKED BY:	DATE:
DESIGN BY:	DATE:
PART NO:	CF20D-XX
SCALE: X:1	UNIT: MM B
DRAWN BY:	DRAWING NO: 9011-1001-000183