


REVISION			
LTR	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	06/15/99	H.T.



Pin Assignment

	HD15 Male	HD15 Female	Mini Din6 Male	Mini Din6 Male
RED CONDUCTORS	1	1	1	1
RED SHIELD	6	6		
GREEN CONDUCTORS	2	2		
GREEN SHIELD	7	7		
BLUE CONDUCTORS	3	3		
BLUE SHIELD	8	8		
	4	4		
	11	11		
	5	5		
	13	13		
	10	10		
	14	14		
	12	12		
	15	15		
	6	6		

ITEM NO.	MATERIAL / SPECIFICATION	QTY REQD	UNIT
6.	3 Mini Coaxial + 4 Pairs, Double Shielded with AL-Foil & Braid + (6 Conductors + Drain Wire) x 2, Beige Outer PVC Jacket	XX	FT.
5.	Beige Molded PVC Hood, Fully Shielded w/AL-FOIL	1	PCS.
4.	Mini Din6 Male W/Gold Plating Contacts	4	PCS.
3.	4/40 Molded Thumbscrew, Color Beige	4	PCS.
2.	HD15 Pin Female W/Gold Plating Contacts	1	PCS.
1.	HD15 Pin Male W/Gold Plating Contacts	1	PCS.

CABLE ASSEMBLY PARTS LIST

UNLESS OTHERWISE SPECIFIED:
 1. DIMENSION ARE IN INCHS
 2. TOLERANCES:
 DECIMALES X.XX ±0.25
 3. DO NOT SCALE DRAWING
 4. REMOVE ALL BURRS AND
 BREAK SHARP EDGES.

PROPRIETARY DOCUMENT
 THIS DRAWING AND/OR INFORMATION ON
 SUBJECT MATTER CONTAINED HEREIN,
 SHALL NOT BE USED, COPIED OR
 DISSEMINATED IN ANY MANNER, OR FOR
 ANY PURPOSE, OTHER THAN AS
 EXPRESSLY STATED BY

CUSTOMER	
R.F.Q. NO.	
DRAWN	DATE
Howie Tseng	06/15/99
CHECKED	
CUSTOMER APPROVAL	

SFCABLE.COM			
1-888-275-8755			
TITLE 3 in 1 Cable for CPU Switch Box (HD15 M/F + (MDIN6 M/M) x 2, Color Beige)			
SIZE	DWG NO.	PART NO.	REV.
	CS20-XX	CS20-XX	A
SCALE: NONE	RELEASE DATE: 06/15/99	SHEET: 1 OF 1	