



MARKING: High Speed HDMI™ Cable E468040 (UL) CL3 75°C 32/3C 28/3C 24/1C  
 \* NOTE: All relevant materials are complied with RoHS directive .

9S01			
P1		P2	
(GREEN) HPD	—————	HPD	(GREEN)
(YELLOW) LY	—————	LY	(YELLOW)
(WHITE) LX	—————	LX	(WHITE)
(ORANGE) UTU	—————	UTU	(ORANGE)
(BLUE) CEC	—————	CEC	(BLUE)
(RED) VCC	—————	+5V	(RED)
(BLACK+DRAIN) GND	—————	GND	(BLACK+DRAIN)
(BROWN) TMDS0	FIBER(OM3)	TMDS0	(BROWN)
(GREEN) TMDS1	FIBER(OM3)	TMDS1	(GREEN)
(ORANGE) TMDS2	FIBER(OM3)	TMDS2	(ORANGE)
(BLUE) CLK	FIBER(OM3)	CLK	(BLUE)

6	HOOD COLOR PVC TRANSPARENT	H1BK01-0304T01		M304
5	(50/125um FIBER*4C+MID) *IC+7/0.08T*3C+ 19/0.08T*3C 41/0.08T*1C+F+D+AL OD:4.8 PVC(CL3 (4K) JACKET BLACK,	A2PE02-0003K09	L-20mm	M3
4	HDMI 19 PIN ZN ALLOY HOOD AND SCREW AND WITH PAD, BRIGHT BLACK(Display 4K UHD Active Optical HDMI)	A6GC21-1295	1set	M1295
3	HDMI 19 PIN ZN ALLOY HOOD AND SCREW AND WITH PAD, BRIGHT BLACK(Source 4K UHD Active Optical HDMI)	A6GC22-1295	1set	M1295
2	HDMI19 MALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, BLUE INSULATOR (FIBER+PCB+GREEN+AFA.H210RXH)	A1KK94-1293	1	M1293
1	HDMI19 MALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, BLUE INSULATOR (FIBER+PCB+RED+AFA.H210TXH)	A1KK93-1293	1	M1293
No.	DESCRIPTION		Q'TY	Supplier

APPROVED		<p><b>SF Cable</b></p> <p>1-888-275-8755</p>	Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU		
DESIGNER	ZHU		
DRAWING	XXX		
DATE	11/JAN/23		
ITEM NO.	HDMI-AOCL34K-XX	UNIT:mm	

CHECKED