



Customer No:	
--------------	--



7	BLACK HEAT SHRINK TUBE $\phi 2.0 \times 5\text{mm}$		A4HA09-0743	5	M743
	BLACK HEAT SHRINK TUBE $\phi 0.8 \times 5\text{mm}$		A4HA08-0959	5	M959
	BLACK HEAT SHRINK TUBE $\phi 2.5 \times 4\text{mm}$		A4HA39-0959	5	M959
	ALUMINUM FOIL 20*60mm		A6MA01-0579	1	M579
	MOLDED PE COLOR TRANSPARENT		A5BA02-0280		M280
	MOLDED PVC BLACK		H1BF01-0304K09		M304
6	BLACK HEAT SHRINK TUBE $\phi 2.0 \times 5\text{mm}$		A4HA09-0743	5	M743
	BLACK HEAT SHRINK TUBE $\phi 0.8 \times 5\text{mm}$		A4HA08-0959	5	M959
	BLACK HEAT SHRINK TUBE $\phi 2.5 \times 4\text{mm}$		A4HA39-0959	5	M959
	ALUMINUM FOIL 33*60mm		A6MA05-0579	1	M579
	MOLDED PE COLOR TRANSPARENT		A5BA02-0280		M280
	MOLDED PVC BLACK		H1BF01-0304K09		M304
5	UL20276 [(28AWG*1Pair+AL+D+MY)*5Pcs+(28AWG*4C)]+AL+DRAIN+AMA BRAID(45%), OD 7.3mm, HDMI1.4, JACKET BLACK, DRAWING No. EAAB2805P2804C-584		H5DC35-0304K09	L-20mm	M304
4	SCREW 5.5*8mm, 4-40#		A6AC01-0095	2	M95
3	HEX-NUT 5*7.7mm 4-40#		A6BC03-0095	2	M95
2	HDMI19 FEMALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, BLACK INSULATOR, WITH PCB		A1KK53-0024	1SET	M24
1	HDMI19 MALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, BLACK INSULATOR		A1KK46-0024	1SET	M24
No.	DESCRIPTION			Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm $\pm 10\text{mm}$ 201~1000mm $\pm 20\text{mm}$ 1001 ~1500mm $\pm 25\text{mm}$ 1501~2100mm $\pm 30\text{mm}$ 2100mm \uparrow $\pm 40\text{mm}$			
CHECKED	HU				
DRAWING	JIANG				
DATE	15/MAR/12	ITEM NO.		UNIT:mm	 