


P1:	M-Y139A
	M-139B
P2,P3:	M-Y139H
	M-139H
P4:	M-426E



1E13					
P2		P1		P3	
1	—————	1	—————	1	BROWN
2	—————	2	—————	2	RED
3	—————	3	—————	3	ORANGE
4	—————	4	—————	4	YELLOW
5	—————	5	—————	5	GREEN
6	—————	6	—————	6	BLUE
7	—————	7	—————	7	PURPLE
8	—————	8	—————	8	GRAY
9	—————	9	—————	9	BLACK
SHIELD	—————	SHIELD	—————	SHIELD	

NOTE: All relevant materials are complied with RoHS directive .

No.	DESCRIPTION	Q'TY	Supplier
5&6	BLACK PVC TUBE ϕ 3.0*22mm	3	M304
	ALUMINUM FOIL 33*65mm	3	M579
	MOLDED PE COLOR TRANSPARENT		M280
	MOLDED PVC BEIGE		M304
4	NON-UL 9C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BEIGE, DRAWING No. EMAL2809C-051	290mm*2	M304
3	MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE	6	M95
2	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	2	M108
1	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M108

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU		
DRAWING	PEGN		
DATE	01/JUN/12		
ITEM NO.	MECY-1MF	UNIT:mm	

CHECKED