



P1,P2: cULus E210037-VN  
 NOTE: All relevant materials are complied with RoHS directive .  
 THE MARKING IS PROTRUDING LETTERING MOULD

CABLE MARKING:

(UL) SJT 3/C 18AWG(0.824MM<sup>2</sup>) VW-1 105°C 300V E204978 C(UL)  
 SJT 3/C 0.824MM<sup>2</sup>(18AWG) FT2 105°C 300V E204978 MSL-VN-

107158B2F18A(FP363-00)			
	P1		P2
BLACK	L	_____	L
WHITE	N	_____	N
GREEN	E	_____	E



No.	DESCRIPTION	Q'TY	Supplier
3	UL SJT 18AWG x 3C, OD 7.8mm, JACKET COLOR SEE LIST, DRAWING No. EPSVT011803C-142	H5TC20-0304K09	L-30mm M304
2	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09	M304
	BRACKET: YS-003	A1QC14-0767	1 M767
1	TERMINAL: 2*4mm, 98740BS-0/A	A1QB55-0257	3 M257
	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09	M304
	TERMINAL WITH BRACKET: M87629LA-3PB	A1QC82-0257K09	1 M257

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU		
DESIGNER	XJW		
DRAWING	ZHU		