



P1,P2:

*NOTE: All relevant materials are complied with RoHS directive .

CONCAVE LETTERING WORD CABLE:

KEMA-KEUR IEMMEQU <VDE> N20050
H03VH2-F 2*0.75mm²MSL

P1	P2
BROWN	BROWN
BLUE	BLUE

3	H03VH2-F 2*0.75mm ² , OD 3.5*5.7mm, JACKET BLACK DRAWING No. EPH3V0107502C-100	H5TG18-0304K09	L-20mm	M304
2	MOLDED PVC 45P, COLOR BLACK	H1BF01-0304K09		M304
	2.35 BRACKET: 8715P	A1QC05-0764	1	M764
1	2.35 TERMINAL: 98714PS-0	A1QB05-0257	2	M257
	MOLDED PVC 45P, COLOR BLACK	H1BF01-0304K09		M304
	TERMINAL: P98003P	A1QA11-0257	1	M257
No.	DESCRIPTION		Q'TY	Supplier

APPROVED					Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm±40mm
CHECKED	HU	17/AUG/17	DRAWN NAME	POWER SUPPLY CORDS & CORDS SETS	
DRAWING	PENG	17/AUG/17	PRODUCT NO.	P-ZIP-06B-G	
UNIT: mm					

REV.3 2017.08.17 MODIFY CONCAVE LETTERING WORD CABLE

REV.2 2012.05.09 MODIFY P1 MODEL WORD

REV.1 2011.03.09 MODIFY P2 MODEL WORD

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm