



P1.P2: E210037

NOTE: All relevant materials are complied with RoHS directive .

MARKING:

(UL) SVT 3/C 18AWG(0.824MM²) VW-1 105°C 300V E204978 CSA SVT 3/C 0.824MM²(18AWG) FT2 105°C 300V 204790 MSL

	P1		P2
BLACK	L	—————	L
WHITE	N	—————	N
GREEN	E	—————	E

No.	DESCRIPTION				Q'TY	Supplier
3	UL SVT 18AWG*3C, OD 6.3mm, JACKET BLACK, DRAWING No. EPSVT011803C-017				H5TB11-0304K09	1800mm M304
2	MOLDED PVC BLACK, 35P				H1BC02-0304K09	M304
	BRACKET: YS-003				A1QC14-0767	1 M767
1	TERMINAL: 2*4mm 98744BS-0/A				A1QB24-0257	3 M257
	MOLDED PVC BLACK, 35P				H1BC02-0304K09	M304
	BRACKET: YS-002				A1QC07-0767	1 M767
1	TERMINAL: 98661BS-1				A1QB01-0257	2 M257
	TERMINAL: Ø4.75, 98475BS-1				A1QB06-0257	1 M257
APPROVED					Unless Otherwise SPEC. Tolerances: 0. ±0.5 .0 ±0.3 .00 ±0.1	
CHECKED	HU	05/AUG/16	DRAWN NAME	POWER SUPPLY CORDS & CORDS SETS		
DRAWING	XIAO	05/AUG/16	PRODUCT NO.	P7B1-06		

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm

