



NEMA 5-15P(MSL-105)

IEC 320 C13(MSL-107)

PACKING B: >3M

PACKING A: <3M

CABLE MARKING:

⚠ (UL) SVT 3/C 18AWG(0.824MM²) VW-1 75°C 300V E204978

SVT 3/C 0.824MM²(18AWG) FT2 60°C 300V 204790 MSL

	P1		P2
BLACK	L	————	L
WHITE	N	————	N
GREEN	E	————	E

P1.P2: E210037



CSA NOTE: All relevant materials are complied with RoHS directive .

3	UL SVT 18AWG*3C, OD 6.3mm, JACKET BLACK SHINY DRAWING No. EPSVT011803C-008	H5TB02-0304K09	L-30mm	M304	
2	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09		M304	
	BRACKET: YS-003	A1QC14-0767	1	M767	
1	TERMINAL: 2*4mm, 98744BS-0/A	A1QB24-0257	3	M257	
	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09		M304	
	BRACKET: YS-002	A1QC07-0767	1	M767	
	TERMINAL: 98661BS-1	A1QB01-0257	2	M257	
	TERMINAL: ø4.75, 321203	A1QB06-0769	1	M769	
No.	DESCRIPTION			Q'TY	Supplier

APPROVED						Unless Otherwise SPEC. Tolerances: 0. ±0.5 .0 ±0.3 .00 ±0.1
CHECKED	HU	18/JUL/14	DRAWN NAME			
DRAWING	CHEN	18/JUL/14	PRODUCT NO.	P7B1-XX	UNIT: mm	

⚠ REV.3	2009.10.22	MODIFY MODEL
⚠ REV.2	2009.09.10	MODIFY CABLE MARKING
⚠ REV.1	2009.09.04	MODIFY LABEL

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm