



CABLE MARKING:

⚠ (UL) SVT 3/C 18AWG(0.824MM²) VW-1 75°C 300V E204978 CSA
 SVT 3/C 0.824MM²(18AWG) FT2 60°C 300V 204790 MSL

	P1		P2
BLACK	L	—————	L
WHITE	N	—————	N
GREEN	E	—————	E

⚠ P1.P2: E210037

NOTE: All relevant materials are complied with RoHS directive .

No.	DESCRIPTION	Q'TY	Supplier
3	UL SVT 18AWG*3C, OD 6.3mm, JACKET BLACK SHINY, DRAWING No. EPSVT011803C-008	L-30mm	M304
2	MOLDED PVC 35P, COLOR BLACK		M304
	BRACKET: YS-003	1	M767
	TERMINAL: 2*4mm, 98744BS-0/A	3	M257
1	MOLDED PVC 35P, COLOR BLACK		M304
	BRACKET: YS-002	1	M767
	TERMINAL: 98661BS-1	2	M257
	TERMINAL: Ø4.75, 98475BS-1	1	M257

⚠ REV.4 2015.01.09	MODIFY MODEL LOGO
⚠ REV.3 2009.10.22	MODIFY MODEL
⚠ REV.2 2009.09.10	MODIFY CABLE MARKING
⚠ REV.1 2009.09.04	MODIFY LABEL

APPROVED				 Unless Otherwise SPEC. Tolerances: 0. ±0.5 .0 ±0.3 .00 ±0.1
CHECKED	HU	09/JAN/15	DRAWN NAME	
			POWER SUPPLY CORDS & CORDS SETS	
DRAWING	ZHU	09/JAN/15	PRODUCT NO.	

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm

UNIT: mm