

AUDIO CABLE

14 AWG / 2 Conductor



Description

14/2 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor		Oxygen Free B.C.
Number of Conductors		2
AWG		14
Stranding		105
Diameter	(inches)	0.0063
Insulation		PVC
Diameter	(inches)	0.1023
Average Thickness	(inches)	0.014
Min. Point Thickness	(inches)	0.013
Assembly Diameter	(inches)	0.2047
Jacket		PVC
Outer Diameter	(inches)	0.2519
Average Thickness	(inches)	0.0236
Min. Point Thickness	(inches)	0.02126
Rip Cord		Nylon
Conductor Resistance	(ohms)	9.2
Nominal Weight	(pounds)	22
Voltage Rating	(volts)	300V

Colors

Insulation Colors Black / Red

Part Numbers

Part Number	Color	Put-up
	Black	500' Reelex II
	White	500' Reelex II

Cable Marking

AUDIO CABLE 2 COND 14AWG HI-STRAND OFC CMR/CL3R FT4 75C
 XXXXXX C(ETL)US ****FT