

## AUDIO CABLE

### 16 AWG / 4 Conductor



#### Description

16/4 Stranded CMR/CL3R Sound Audio Cable

#### Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

#### Physical Characteristics

Conductor		Oxygen Free B.C.
Number of Conductors		4
AWG		16
Stranding		65
Diameter	(inches)	0.0063
Insulation		PVC
Diameter	(inches)	0.0827
Average Thickness	(inches)	0.0122
Min. Point Thickness	(inches)	0.0106
<b>Assembly Diameter</b>	(inches)	0.2008
Jacket		PVC
Outer Diameter	(inches)	0.248
Average Thickness	(inches)	0.0236
Min. Point Thickness	(inches)	0.0213
Rip Cord		Nylon
Conductor Resistance	(Ohms)	15.5
Nominal Weight	(pounds)	27

#### Colors

Insulation Colors Black / Red / White / Green

#### Part Numbers

Part Number	Color	Put-up
	Black	500' Reelex II
	White	500' Reelex II

#### Cable Marking

AUDIO CABLE 4 COND 16AWG HI-STRAND OFC CMR/CL3R FT4 75C  
 XXXXXX C(ETL)US \*\*\*\*FT