



MARKING:

(UL) SJT 3/C 14AWG(2.08MM²) VW-1 105°C 300V E204978 CSA
 SJT 3/C 2.08MM²(14AWG) FT2 105°C 300V 204790 MSL

107131B2F14A(FP248-00)

P1 P2

BLACK L ——— L
 WHITE N ——— N
 GREEN E ——— E

NEMA 6-15P(MSL-131)

IEC 320 C13(MSL-107)

PACKING:

P1,P2: cULus E210037

*NOTE: All relevant materials are complied with RoHS directive .
 THE CABLE MARKING IS CONCAVE LETTERING MOULD

| No. | DESCRIPTION | Q'TY | Supplier |
|-----|---|----------------|----------|
| 3 | UL SJT 14AWG x 3C, OD 9.3mm, JACKET BLACK, DRAWING No. EPSVT011403C-147 | Xmm | M304 |
| 2 | MOLDED PVC 35P, COLOR BLACK | H1BC02-0304K09 | M304 |
| | BRACKET: YS-003 | A1QC14-0767 | 1 M767 |
| | TERMINAL: 2*4mm, 98744L | A1QB42-0257 | 3 M257 |
| 1 | MOLDED PVC 35P, COLOR BLACK | H1BC02-0304K09 | M304 |
| | BRACKET: NEMA 6-15P(ZHS-425) MSL-131 COLOR BLACK | A1QC62-0767 | 1 M406 |
| | TERMINAL: 98661BS-1 | A1QB01-0257 | 2 M257 |
| | TERMINAL: Ø4.75mm 98475BS-1 | A1QB06-0257 | 1 M257 |

APPROVED

Cable Length Unless Other Spec. Tolerances:
 0 ~200mm ±10mm
 201~1000mm ±20mm
 1001 ~1500mm ±25mm
 1501~2100mm ±30mm
 2100mm↑ ±40mm

CHECKED HU 07/SEP/18 DRAWN NAME POWER SUPPLY CORDS & CORDS SETS

DRAWING ZHU 07/SEP/18 PRODUCT NO. SF-C13615P-XX UNIT: mm

REV.2 2018.09.07 UPDATE PICTURE
 REV.1 2018.02.26 MODIFY MSL-131 TERMINAL BASSET SIZE & BRACKET
 NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm