

P1: M-071A

Customer No.: NO.1


P2: M-072A



PACKING A: <1FT

PACKING B: <2FT

PACKING C: >2FT



* NOTE: ALL relevant materials are complied with RoHS directive.
THE MARKING IS CONCAVE LETTERING MOULD

3	UL SJTW 10AWG*3C OD 14.6mm, JACKET BLACK, DRAWING No. EPSJT011003C-202	H5TC56-0304K09	L-30mm	M304
2	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09		M304
	BRACKET: HC-05200-08AW0(NEMAL6-30R)	A1QC68-0406K09	1	M406
	TERMINAL: 95757BS-0	A1RT16-0257	2	M257
	TERMINAL: 95758BS-0(G)	A1RT18-0257	1	M257
1	MOLDED PVC 35P, COLOR BLACK	H1BC02-0304K09		M304
	BRACKET: YST-FB-6-30P(NEMAL6-30P)	A1QC78-0767	1	M767
	TERMINAL: 95657	A1RQ34-0257	1	M257
	TERMINAL: 95658	A1RQ35-0257	1	M257
	TERMINAL: 95659	A1RQ36-0257	1	M257

No.	DESCRIPTION	Q'TY	Supplier
APPROVED			
CHECKED	HU		
DESIGNER	ZHU		
DRAWING	ZY		
DATE	29/OCT/22	ITEM NO.	SF-L630SFR-XX

SFCable
— 1-888-275-8755 —

Cable Length Unless Other Spec.
Tolerances:
0 ~200mm ±10mm
201~1000mm ±20mm
1001 ~1500mm ±25mm
1501~2100mm ±30mm
2100mm ↑ ±40mm

P1: cULUS E210037-VN

P2: cULUS E210037-VN

MARKING: (UL) SJTW 3/C 10AWG(5.26MM²) VW-1 105°C 300V E204978 C (UL)
SJTW 3/C 5.26MM²(10AWG) FT2 105°C 300V E204978 MSL

10W1-L630PR-XX	
P1	P2
BLACK Y	X
WHITE X	Y
GREEN G	G

NOTE: Cable Length Unless Otherwise Spec. Tolerances: Under 6FT ±25mm; Another ±50mm

