



9501-14			
P1		P2	
1	—————	1	RED 20#
2	~~~~~	2	WHITE
3	~~~~~	3	GREEN
4	—————	4	BLACK 20#
SHIELD	—————	SHIELD	

NOTE: All relevant materials are complied with RoHS directive .

6	MOLDED PVC BLACK		M304
5	MOLDED PVC BLACK		M304
4	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 20AWG, AMA BRAID, OD 5.0mm, JACKET BLACK, DRAWING No.EUAB2801P2002C-187	6080mm	M304
3	FERRITE CORE 14.3*6.35*28.5mm	1	M113
	MOLDED PVC BLACK		M304
2	USB B MALE 2.0, GOLD PLATING 30U" ON CONTACTS&METAL HOOD, WHITE INSULATOR, SHORT TYPE	1set	M108
1	USB A MALE 2.0, GOLD PLATING 30U" ON CONTACTS&METAL HOOD, WHITE INSULATOR, SHORT TYPE	1set	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm± ±40mm	
CHECKED	TIAN		
DRAWING	LI		
DATE	05/SEP/08		
ITEM NO.	UB12-20	UNIT:mm	

**sfcable.com**

CHECKED