



MARKING: HI-SPEED USB Revision 2.0 SHIELDED 28AWG/2C+24AWG/2C (UL) E305668 TYPE CM 75°C CSA 204790 TYPE CM 75°C MSL

* NOTE: All relevant materials are complied with RoHS directive .

9461-47			
P1		P2	
1	—	1	RED 24#
2	—	2	WHITE
3	—	3	GREEN
4	—	4	BLACK 24#
SHIELD	—	SHIELD	SHIELD+BRAID

5	MOLDED PVC BEIGE	H1BF01-0304K09		M304
4	MOLDED PVC BEIGE	H1BF01-0304K09		M304
3	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG, AMA BRAID 64% SHIELDING WITH DRAIN WIRE,OD 4.5mm,JACKET BEIGE,DRAWING No.EUAB2801P2402C-139	H5KH29-0304K09	L-20mm	M304
2	USB B MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	A1HB15-0454	1set	M454
1	USB A MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT A PIERCE TYPE	A1HA22-0454	1set	M454
No.	DESCRIPTION		Q'TY	Supplier

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm		
CHECKED	HU				
DRAWING	ZHU				
DATE	04/JUN/19	ITEM NO.	UB12-XX-OFFWHT	UNIT:mm	