



Length(L)	Length(X)
915mm	895mm
1830mm	1810mm
3050mm	3030mm
4570mm	4550mm

**⚠ CABLE MARKING:** E300060    ϰ    AWM 2725 80°C 30V VW-1    cϰ AWM E300060  
 I /II    A/B 80°C 30V FT1 MSL -VN-    USB3.2

**⚠** \* NOTE: All relevant materials are complied with RoHS directive .

9142-14	
P1	P2
1 —————	1 RED
2 ————X———	2 WHITE
3 ————X———	3 GREEN
4 —————	4 BLACK
5 ————X———	8 BLUE
6 ————X———	9 YELLOW
7 —————	7 SHIELD
8 ————X———	5 PURPLE
9 ————X———	6 ORANGE
7 —————	7 SHIELD
SHIELD ————	SHIELD

3	BLACK HEAT SHRINK TUBE $\phi$ 1.0*4mm	A4HA78-AAAA	2	MAAAA
	BLACK HEAT SHRINK TUBE $\phi$ 1.5*8mm	A4HA40-AAAA	4	MAAAA
	MOLDED PVC BLACK	H1BF01-0304K09		M304
2	USB3.2 Gen1x1 CABLE, 28AWG*1PAIR+(28AWG*1PAIR+D+F-AL)*2PCS +24AWG*2C+AMA BRAID(85%), OD 5.8mm JACKET BLACK, DRAWING NO. EUAB2801P2802P2402C-333	H5KS02-0304K09	Xmm	M304
1	USB3.2 Gen1x1, GOLD FLASH ON CONTACTS, BLUE INSULATOR, SHORT TYPE	A1HA48-0454	2set	M454
No.	DESCRIPTION		Q'TY	Supplier

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm    ±10mm 201~1000mm    ±20mm 1001 ~1500mm    ±25mm 1501~2100mm    ±30mm 2100mm↑    ±40mm
CHECKED	HU		
DESIGNER	XJW		
DRAWING	DAI		
DATE	02/APR/24		
ITEM NO.	USB3-AA-XX	UNIT:mm	

**⚠** REV.3 2024.04.02    MODIFY MARKING

**⚠** REV.1 2023.3.10    MODIFY MARKING

**⚠** REV.2 2023.12.29    MODIFY MARKING    CHECKED